

Continuous inkjet

9750+: The true value of innovation



The innovation you need. The experience you trust.

Markem-Imaje delivers even more flexibility and stability with our next-generation model, the 9750+.

Backed by decades of building dependable inkjet printers, the 9750+ breakthrough ink circuit—with its unique capacity to manage all types of inks, including contrast pigment inks for premium permanence and legibility—takes inventory streamlining and modularity to the next level. Meticulously engineered and qualified by the most modern methods, the 9750+'s latest enhancements bring you:

- Technology leaps grounded in time-tested industrial processes for maximized uptime, reduced maintenance
- Cutting-edge design with simplified UI and modular components for easy operation, maintenance or repair
- Clear, customizable and traceable black or colored codes that meet customers' growing demand for supply chain visibility and inventory streamlining

Key benefits

Enhanced ink circuit taking dye or pigmented inks

Advanced R&D backed by proven industrial processes and methods

- Intelli'Inks system ensures optimal coder performance and flexibility when coding different package materials in all colors, with all inks
- Intelli'Swap technology streamlines mechanicals down to swappable modules
- Jet Speed Control technology automatically adjusts ink and printer variables to ensure drop placement, quality and code consistence. Every time.

Sustainability

More sustainable solutions = Long-term value and lower TCO*


- Intelli'Swap modularity enables you swap out only the individual parts that need to be replaced and not the entire block
- Intelli'Design process and a portfolio of rigorously developed ink formulations help reduce consumable consumption and VOC* emissions by up to 50% while improving operator safety, well-being and TCO
- Consumable-saving mode additionally reduces consumption and waste

Digitalization

Convenience only a couple clicks away

- Our Connected Printer Services powered by a secure IoT platform*, allow for a predictive analysis and therefore help maximize uptime, achieve OEE* objectives
- Consumable and spare part supply through online portal
- Quick customizable 24-pin interface allows for easy integration in a 4.0 connected environment

9750 continuous inkjet specifications



Print features

Mono-jet printhead

G head (printing resolution: 71 dpi) M head (printing resolution: 115 dpi)

Up to 5 lines of print Print speed: up to 6.6 m/s Font height from 5 to 32 dots

Character height: from 1.2 to 11.2 mm

Wide choice of 1D and 2D barcodes: EAN 8/EAN 13/UPCA /UPCE barcodes, code 39, interleaved 2 of 5, Datamatrix, QRcode, Dotcode, GS1 standard compliant

Wide choice of characters: Latin, Arabic, Cyrillic, Hebrew, Japanese, Chinese, Korean, etc.

Other characteristics

Weight: 25 kg

Table-top or vertical mounting

Ultra-flexible 3-meter umbilical cable

Stainless steel cabinet and printhead case

Dust/water ingress protection rating: IP56 requiring no plant air

Operating temperature range: 32 °F to 122 °F (0 °C to 50 °C) depending on ink used

Humidity: 10 to 90% non-condensing Electrical power supply: 100-240 V; 1,6 A;

frequency 50/60 Hz; 30 W

Operations

WYSIWYG 10-inch capacitive color touchscreen: realtime display of remaining print capacity expressed in hours and number of messages; integrated assistance and alert system; simplified message printing and management; creation of user profiles; tracking of consumption and printer availability

Message library (up to 1,000 messages)

Automatic selection of fonts, depending on print speed and printhead/object distance

Specific date management (rounding date function)
Parent/child connectivity

Jet Speed Control guarantees marking quality Printhead with embedded intelligence for high marking quality and reduced maintenance

Broad range of dye and pigment inks: multi-use, high performance; alcohol based, ketone-free and MEK-free inks

Sealed 0.6 and 08-liter consumable cartridges with fool proofing system

Compact and modular ink circuit for better thermal management and controlled additive consumption

100% front access modular ink circuit for a simplified preventive maintenance

Quick connect/disconnect of accessories (photocell, alarm and encoder)

Enhanced native connectivity including USB, Ethernet, serial and a configurable M12 connector for I/O

Remote services

Our intelligent self-support solution. Live helpdesk support with remote video capabilities

Markem-Imaje Connected Printer Services powered by a secure IoT platform**

Options

Ultra-flexible 6-meter umbilical cable

Consumable saving mode for up to -60% additive consumption: at 20 °C less than 3,5 cc/h for MEK-based ink or less than 2cc/h for MEK-free ink

Printhead pressurization kit

Air blade kit

Many I/O possibilities including a configurable single point connector (24 pins)

Accessories

Wide range of accessories

Printer supports: stands (stainless steel or aluminum), table or wall mounting brackets

Printhead supports: stand (stainless steel) and choice of brackets

Pigment ink shaker

Photocells

ncoders

Alarm beacons (24 V)

Set of pre-cabled connectors M12, Ethernet IP66

Software

Fully compatible with CoLOS® Version 6.3 Service Pack onwards

Logo creation with CoLOS® Version 6.4 Graphics software

*TCO: Total cost of ownership. VOC: Volatile organic compounds. OEE: Overall equipment effectiveness. **Internet of things, please check availability in your country

