

DM5 Dynapail™

WITH IT'S SIMPLICITY, INNOVATION AND FLEXIBILITY, THE DM5 DYNAPAIL™ PROVIDES UNINTERRUPTED FLOW OF HOT MELT ADHESIVE TO MEET YOUR SPECIFIC PRODUCTION DEMANDS. THE DM5 DYNAPAIL WORKS WITH A VARIETY OF ADHESIVE TYPES, INCLUDING PUR.

SIMPLICITY

Removable, replaceable platen faces provide ultimate ease of maintenance.

INNOVATION

Options for multiple adhesive applications including manual, swirl and automatic.

FLEXIBILITY

Platen faces are available for various reactive and non-reactive adhesives, including PUR.



DM5 Dynapail™ ADHESIVE PAIL MELTER

The DM5 Dynapail™ adhesive pail melter provides uninterrupted flow of hot melt adhesive. Daily operations are simplified with the DM5 Dynapail's™ standard features, which include field-interchangeable platen faces, self-diagnostics, multiple temperature control sensors, and low/empty drum indicators.

FEATURES

- Unique platen designs provide excellent platen force, melt rates, adhesive transfer for most adhesive types including PUR.
- Compact footprint provides flexibility and ease of installation.
- A removable platen face allowing for field retrofit, saving you time and money. The removable platen face allows more accessibility for maintenance and cleaning.

OPTIONS

- Digital Pressure Transducer Kit
- Swirl Kit, Dual, 240V
- Vent hood for PUR adhesive applications
- Finned, High Flow, Standard Air Inject

TECHNICAL DATA

Operating temperature range	40°C to 232°C (100°F to 450°F)
Melt rate *	up to 14 kg/hr (30lbs/hr)*
Gear pump sizes	0.55 ccm-10 ccm
Pail size	5 gallon (19l) steel pail US standard
Pail inner diameter	11.25 in (30cm)
Hose/Head output zones	2/2
Aux output zones	2
Supply voltage setup 1	240 VAC Delta, 480 VAC Delta
Supply voltage setup 2	400 VAC WYE
Total Amp draw	6.7 kW
Height	165 cm (64.9in)
Depth	65 cm (25.6in)
Width	114.3 cm (45.0in)

* Melt rates vary with adhesive type

LOCATIONS

Americas

ITW Dynatec
31 Volunteers Drive
Hendersonville, TN 37075
Phone: +1.615.824.3634
Fax: +1.615.264.5248
info@itwdynatec.com
www.itwdynatec.com

China

ITW Dynatec Suzhou
No.2 Anzhi Street
SIP, Suzhou, 215122, China
Phone +86.512.6289.0620
Fax +86.512.6289.0621
info@itwdynatec.cn
www.itwdynatec.cn

Japan

ITW Dynatec K.K
Flos Kamata
26-11, Nishikamata 7-chome
Ota-ku, Tokyo 144-0051, Japan
Phone: +81.3.5703.5501
Fax: +81.3.5703.5505
info@itwdynatec.co.jp
www.jp.itwdynatec.com

Europe, Middle East and Africa

ITW Dynatec GmbH
Industriestraße 28
40822 Mettmann, Germany
Phone: +49.2104.915.0
Fax: +49.2104.915.111
info@itwdynatec.de
www.itwdynatec.de

